

What is claimed is:

1. A vertically aligned liquid crystal display device for controlling liquid crystal molecules alignment in voltage application by providing linear structures or linear slits consisting of a plurality of  
5 constituent units to at least one of a pair of substrates having an electrode thereon, comprising:

alignment controlling means for forming an alignment singular point  $s=-1$  of liquid crystal molecules at an intersecting point between the structures on the electrode or the slits in the electrode and an edge of a pixel electrode on one of the substrates.

2. A liquid crystal display device according to claim 1, wherein the linear structures are formed on  
15 the pixel electrode or a common electrode.

3. A liquid crystal display device according to claim 1, wherein the slits are not formed on the edge of the pixel electrode located on prolonged lines of  
20 the slits.

4. A liquid crystal display device according to claim 1, wherein the structure is divided on or over the edge of the pixel electrode.

5. A vertically aligned liquid crystal display device for controlling liquid crystal molecules alignment in voltage application by providing linear  
25 structures or linear slits consisting of a plurality of

09662236 "091400

constituent units to at least one of a pair of substrates having an electrode thereon, comprising:

alignment controlling means for forming an alignment singular point  $s=+1$  of liquid crystal molecules at an intersecting point between the structures or the slits formed on one substrate and an edge of a pixel electrode formed on the other substrate.

6. A vertically aligned liquid crystal display device for controlling liquid crystal molecules alignment in voltage application by providing linear structures or linear slits consisting of a plurality of constituent units having a bending portion to at least one of a pair of substrates having an electrode thereon,

wherein the bending portions of the structures or the slits on one of the substrates having a pixel electrode are put out from the edge of the pixel electrode.

7. A vertically aligned liquid crystal display device for controlling liquid crystal molecules alignment in voltage application by providing linear structures or linear slits consisting of a plurality of constituent units having a bending portion to at least one of a pair of substrates having an electrode thereon,

wherein the bending portions of the structures or the slits arranged on the other substrate to oppose to a pixel electrode on one substrate are not arranged on the edge of the pixel electrode.

00662236-091400

Spec (1)

10

15

20

25

Common  
not on  
edge

5' x 1

8. A thin film transistor substrate comprising:  
a storage capacitance forming electrode formed on  
a first substrate;

an active element formed on the first substrate;  
5 and

a pixel electrode formed on the first substrate to be  
connected to the active element, and divided into at  
least three areas by slits;

wherein electrical connection of one area of the  
10 three areas of the pixel electrode to another area has  
a plurality of routes passing through different areas.

9. A thin film transistor substrate according to  
claim 8, wherein at least two of the routes of the  
electrical connection are provided to oppose  
15 electrically to the storage capacitance forming  
electrode.

10. A thin film transistor substrate according to  
claim 9, wherein areas opposing to the storage  
capacitance forming electrode are different every route  
20 opposing to the storage capacitance forming electrode.

11. A thin film transistor substrate according to  
claim 9, wherein thicknesses of dielectric layers are  
different in areas opposing to the storage capacitance  
forming electrode every route opposing to the storage  
25 capacitance forming electrode.

12. A thin film transistor substrate according to  
claim 9, wherein storage capacitance values are

004160" 9229960

different every route opposing to the storage capacitance forming electrode.

13. A liquid crystal display device including a thin film transistor substrate set forth in any one of claims 8 to 12.

14. A liquid crystal display device in which liquid crystal having negative dielectric anisotropy is sealed between a first substrate and a second substrate, to surfaces of which a vertical alignment process is applied, and alignment of the liquid crystal molecules becomes substantially perpendicular when no voltage is applied, substantially parallel when a predetermined voltage is applied, and oblique when a voltage smaller than the predetermined voltage is applied, comprising:

a first domain defining means formed of dielectric projections provided on the first substrate, for defining an oblique alignment direction of the liquid crystal molecules when the voltage smaller than the predetermined voltage is applied;

a second domain defining means provided on the second substrate, for defining the oblique alignment direction of the liquid crystal molecules when the voltage smaller than the predetermined voltage is applied;

a plurality of first bus lines formed on the first substrate or the second substrate;

a plurality of second bus lines formed over the

00466236 091400

first

20  
second

25

first bus lines at a distance;

a pixel electrode formed in areas that are partitioned by the first bus lines and the second bus lines; and

5 dielectric structures formed on at least one of the first substrate and the second substrate in areas to oppose to at least a part of areas between the pixel electrode and the first bus lines, the dielectric structures being different from the projections.

10 15. A liquid crystal display device according to claim 14, wherein the projections and the dielectric structures are formed of same material and by same steps.

15 16. A liquid crystal display device according to claim 14, wherein the dielectric structures are formed on at least one of the first bus lines and the second bus lines.

20 17. A liquid crystal display device according to claim 14, wherein the second domain defining means are projections to protrude into a layer of the liquid crystal or slits opened partially in an electrode on a second substrate side.

25 18. A liquid crystal display device according to claim 14, wherein a red, green, or blue color filter is formed to oppose to the pixel electrode, and the dielectric structures are composed of color filters that are overlapped in areas not opposing to the pixel

004T60" 9E229960

electrode.

19. A liquid crystal display device according to claim 18, wherein the areas not opposing to the pixel electrode are at least one of areas between the first  
5 bus lines and the pixel electrode and areas between the second bus lines and the pixel electrode.

20. A liquid crystal display device according to claim 18, wherein another dielectric structures are further superposed on the areas in which the color  
10 filters are overlapped.

21. A liquid crystal display device according to claim 18, wherein another dielectric structures are formed to oppose to the areas in which the color  
filters are overlapped.

22. A liquid crystal display device according to claim 14, wherein the dielectric structures are formed  
15 up to areas protruding into a part of the pixel electrode.

23. A liquid crystal display device according to claim 14, wherein at least one of the first domain  
20 defining means and the second domain defining means is not provided on an outside of the pixel electrode, or is not provided in peripheral areas intersecting with at least one of the first bus lines and the second bus  
25 lines.

24. A liquid crystal display device according to claim 14, wherein a thickness of the dielectric

004662236-091400

structures is more than 1  $\mu\text{m}$ .

25. A liquid crystal display device comprising:

a first substrate and a second substrate arranged in parallel with each other at a distance;

5 a liquid crystal layer formed by filling liquid crystal material having negative dielectric anisotropy between the first substrate and the second substrate;

a first electrode and a second electrode formed on opposing surfaces of the first substrate and the  
10 second substrate respectively to define a pixel by at least one of them;

projections formed on the opposing surface of the first electrode;

a domain defining means formed on the opposing  
15 surface of the second electrode, for defining boundary positions of domains in which tilt directions of liquid crystal molecules are uniform together with the projections;

an alignment film formed on at least one of the  
20 first substrate and the second substrate and having an alignment defining force to align the liquid crystal molecules on a surface of the alignment film perpendicularly to a film surface; and

a compensating means arranged along edges of the  
25 projections when viewed along a normal direction of the first substrate, for reducing a double refraction effect acting on a light, that transmits in a thickness

004160-9229960

direction of the liquid crystal layer, due to oblique alignment of the liquid crystal molecules of the liquid crystal layer in a neighborhood of the edges of the projections.

5           26. A liquid crystal display device according to claim 25, wherein the compensating means is formed of optical member which is arranged along the edges of the projections on a non-opposing surface of the first substrate and formed of material having refractive  
10           anisotropy.

          27. A liquid crystal display device according to claim 25, wherein the projections contain a first portion positioned in a neighborhood of the edge and having refractive anisotropy and a second portion  
15           positioned in a center portion having no refractive anisotropy or smaller refractive anisotropy than the first portion respectively, and the first portions are also used as the compensating means.

          28. A liquid crystal display device comprising:  
20           a first substrate and a second substrate arranged in parallel with each other at a distance;

          a liquid crystal layer formed by filling liquid crystal material having negative dielectric anisotropy between the first substrate and the second substrate;

25           a first electrode and a second electrode formed on opposing surfaces of the first substrate and the second substrate respectively to define a pixel by at

004760" 9E22960



least one of them;

an alignment film formed on at least one of the first substrate and the second substrate and having an alignment defining force to align the liquid crystal molecules of the liquid crystal layer perpendicularly to the film surface;

projections formed on the opposing surface of the first electrode;

10        a first domain defining means provided on the opposing surface of the first electrode and having a pattern elongated along one direction in at least a local area within a substrate surface, and for tilting the liquid crystal molecules in a neighborhood of an edge of the first domain defining means to such a  
15        direction that end portions positioned far from the first electrode go away from the first domain defining means when a voltage is applied between the first electrode and the second electrode; and

20        a second domain defining means provided on the opposing surface of the second electrode and arranged in parallel with or to be overlapped with the first domain defining means in at least a local area within the substrate surface when viewed along a normal direction of the substrate, and for tilting the liquid  
25        crystal molecules on an inside of the second domain defining means to a direction that is substantially parallel with a length direction of the second domain

0966236-091400

defining means.

29. A liquid crystal display device according to claim 28, wherein the first domain defining means contains projections formed of dielectric material formed on the first electrode or slits formed in the first electrode, and

the second domain defining means contains projections formed on the opposing surface of the second substrate and having a conductive surface, areas of the alignment film which are formed on the opposing surface of the second substrate and in which an alignment defining force is destroyed or weakened, or recess patterns on the surface of the dielectric film formed on the opposing surface of the second substrate.

30. A liquid crystal display device according to claim 28, further comprising:

a third domain defining means formed on the opposing surface of the first substrate to extend in a direction orthogonally intersecting with the first domain defining means in at least a local area within the substrate surface, and for tilting the liquid crystal molecules of the liquid crystal layer in a neighborhood of an edge of the third domain defining means to such a direction that end portions positioned far from the first electrode go away from the third domain defining means when the voltage is applied between the first electrode and the second electrode.

31. A liquid crystal display device comprising:  
a first substrate and a second substrate arranged  
in parallel with each other at a distance;

5 a liquid crystal layer formed by filling liquid  
crystal material having negative dielectric anisotropy  
between the first substrate and the second substrate;

10 a first electrode and a second electrode formed  
on opposing surfaces of the first electrode and the  
second electrode respectively to define a pixel by at  
least one of them; and

15 an alignment film formed on at least one of  
opposing surfaces of the first substrate and the second  
substrate, and defined into first areas containing at  
least two parallel patterns elongated in one direction  
and a second area between the first areas, the second  
area having an alignment defining force to align liquid  
crystal molecules of the liquid crystal layer  
perpendicularly to the substrate surface and the first  
areas having no alignment defining force or a weaker  
20 alignment defining force than the alignment defining  
force in the second area.

32. A liquid crystal display device according to  
claim 31, wherein a chiral agent is added into the  
liquid crystal layer.

25 33. A liquid crystal display device comprising:

a first substrate and a second substrate arranged  
in parallel with each other at a distance;

004T60"9E22966

a liquid crystal layer formed by filling liquid crystal material having negative dielectric anisotropy between the first substrate and the second substrate;

5 a first electrode and a second electrode formed on opposing surfaces of the first electrode and the second electrode respectively to define a pixel by at least one of them; and

10 an alignment film formed on at least one of opposing surfaces of the first substrate and the second substrate, and defined into first areas extended from respective corners of the pixel to an inside of the pixel to have patterns connected mutually and a second area partitioned by the first areas and edges of the pixel, the second area having an alignment defining  
15 force to align liquid crystal molecules of the liquid crystal layer perpendicularly to the substrate surface and the first areas having no alignment defining force or a weaker alignment defining force than the alignment defining force in the second area.

20 34. A liquid crystal display device comprising:  
a first substrate on which a first electrode and bus lines for transmitting a signal to the first electrode are formed;

25 a second substrate on which a second electrode is formed;

domain defining projections provided on one of the first substrate and the second substrate;

004460" 9229960

a plurality of domain defining slits provided on an electrode on the other of the first substrate and the second substrate to be aligned on a straight line;

5 a first alignment film for covering the first electrode;

a second alignment film for covering the second electrode; and

10 liquid crystal sealed between the first substrate and the second substrate and having negative dielectric anisotropy;

15 wherein a pre-tilt angle revealing process is applied to the alignment film on the other substrate in an area in which alignment of liquid crystal molecules becomes unstable by a lateral electric field from the bus line.

20 35. A liquid crystal display device according to claim 34, wherein the pre-tilt angle revealing process sets a pre-tilt angle at an interface between the alignment film and the liquid crystal to more than 45 degrees but less than 90 degrees when no voltage is applied.

36. A liquid crystal display device according to claim 34, further comprising:

25 auxiliary projections provided on one substrate to be arranged along the edge of the electrode on the other substrate.

37. A liquid crystal display device according to

00460-9229960

claim 36, wherein the pre-tilt angle revealing process is applied to areas in which an angle between the domain defining projections and the edge of the pixel electrode is an obtuse angle.

5           38. A liquid crystal display device according to claim 34, wherein the pre-tilt angle revealing process is applied to a bus line side areas in the slits whose end portions on the bus line side are closed and which are positioned closest to the bus line.

10           39. A liquid crystal display device comprising:  
a first substrate on which a first electrode and a bus line for transmitting a signal to the first electrode are formed;

15           a second substrate on which a second electrode is formed;

domain defining projections provided on one of the first substrate and the second substrate;

20           a plurality of domain defining slits provided on the electrode on the other of the first substrate and the second substrate to be aligned on a straight line; and

liquid crystal sealed between the first substrate and the second substrate and having negative dielectric anisotropy;

25           wherein a width of a bus line opposite side end of a first slit of the plurality of slits, that is positioned closest to the bus line, is set smaller than

004760" 9229960

a width of a bus line side end of a second slit positioned adjacent to the first slit.

40. A liquid crystal display device according to claim 39, further comprising:

5           auxiliary projections provided on one substrate to be arranged along the edge of the electrode on the other substrate.

41. A liquid crystal display device comprising:

10           a first substrate on which a first electrode and a bus line for transmitting a signal to the first electrode are formed;

            a second substrate on which a second electrode is formed;

15           domain defining projections provided on one of the first substrate and the second substrate;

            a plurality of domain defining slits provided on the electrode on the other of the first substrate and the second substrate to be aligned on a straight line;

20           a first alignment film for covering the first electrode;

            a second alignment film for covering the second electrode; and

25           liquid crystal sealed between the first substrate and the second substrate and having negative dielectric anisotropy;

            wherein a pre-tilt angle revealing process is applied to the alignment film on the other substrate in

004760-9229960

an area in which alignment of liquid crystal molecules becomes unstable by a lateral electric field from the bus line, and a width of a bus line opposite side end of a first slit of the plurality of slits, that is positioned closest to the bus line, is set smaller than a width of a bus line side end of a second slit positioned adjacent to the first slit.

42. A liquid crystal display device in which liquid crystal is sealed between a pair of substrates on which electrodes are provided,

wherein a domain defining portion is provided on one substrate of the pair of substrates,

a dielectric film having a high dielectric constant portion and a low dielectric constant portion is provided on the other substrate of the pair of substrates, and

the high dielectric constant portion is arranged at positions in an oblique direction to the domain defining portion and the low dielectric constant portion is arranged at positions opposing to the domain defining portion, and difference in a relative dielectric constant between the high dielectric constant portion and the low dielectric constant portion is more than 0.5.

43. A liquid crystal display device according to claim 42, wherein slits are formed in the electrode on one substrate as the domain defining portion.



44. A liquid crystal display device according to claim 42, wherein projections are provided on one substrate as the domain defining portion.

5 45. A liquid crystal display device according to claim 42, wherein dielectric constant is changed stepwise between the high dielectric constant portion and the low dielectric constant portion.

004150" 9E229960